

Spartan Chemical Company, Inc. **Material Safety Data Sheet**

SECTION I: PRODUCT INFORMATION

Product Name or Number (as it appears on label): SPARCLEAN SILVERWARE PRE-SOAK [57]

Product Number: 7657

1110 Spartan Drive

Maumee OH 43537

Product Division: Janitorial

Product/Technical Information: 1-(800)-537-8990 Spartan Chemical Company, Inc.

Medical Emergency: 1-(888)-314-6171 (24 hours)

Chemical Leak/Spill Emergency: CHEMTREC 1-(800) 424-9300 (24 hours)

Shipping Description: Non-Hazardous Products

NFPA Ratings:	HMIS Ratings:
Health: 1- Slight	Health: 1- Slight
Fire: 0 - Minimal	Fire: 0 - Minimal
Reactivity: 0 - Minimal	Reactivity: 0 - Minimal
	Pers. Prot. Equip.: See Section VIII

SECTION II: HAZARDOUS INGREDIENTS

(Listed when present at 1% or greater, carcinogens at 0.1% or greater) All component chemicals are listed or exempted from listing on the "TSCA Inventory" of chemical substances maintained by the U.S. Environmental Protection Agency.

			Table Z-1-A			
Chemical Name(s)	%Wt	CAS Registry No.	TWA mg/m³	STEL mg/m³	CEILING mg/m³	NTP, IARC or OSHA Carcinogen
Alcohol ethoxylate	1-5	68439-46-3	Not Established	Not Established	Not Established	No
Triethanolamine	1-5	102-71-6	5 (ACGIH)	Not Established	Not Established	No
Alcohol ethoxylate	1-5	34398-01-1	Not Established	Not Established	Not Established	No
Dicarboxylic fatty acid	1-5	53980-88-4	Not Established	Not Established	Not Established	No
Alpha-amylase	< 1.0	9000-90-2	Not Established	Not Established	Not Established	No
Protease	< 1.0	9014-01-1	Not Established	Not Established	0.00006 ACGIH	No
Mannanase	< 1.0	37288-54-3	Not Established	Not Established	Not Established	No

SECTION III: PHYSICAL DATA

Boiling Point: 212 °F	Vapor Pressure: Not determined
Vapor Density (AIR = 1): Unknown	Solubility in Water: Complete
pH: 7.5-8.0	Specific Gravity (H ₂ O=1): 1.007
Evaporation Rate (but.ace.=1): <1	Percent Solid by Weight: 5-10
Physical State: Liquid	
Appearance & Odor: Croon liquid mild odor	

SECTION IV: FIRE & EXPLOSIVE HAZARD DATA

Flash Point: > 212°	°F	Method Used: ASTM-D56
Flammable Limits: Not Es	stablished	Flame Extension: N/A
Extinguishing Media: Produ	uct does not support combustion	. Use extinguishing media appropriate for surrounding fire.
Special Fire Fighting Procedures: Wear		d breathing apparatus and protective clothing. Cool fire-exposed
Unusual Fire & Explosive Hazards: Comb	bustion products are toxic.	

SECTION V: HEALTH HAZARD DATA					
Threshold Limit Value:				Entry: Inhalation, Skin Contact, Eyes and Oral	
Effects of Overexposure- Conditions to Avoid:	 Causes eye irritation: Symptoms may include pain, redness, swelling and tearing May cause skin irritation: Symptoms may include pain, redness and swelling. May be harmful if swallowed: Symptoms may include nausea, vomiting, pain and diarrhea. Inhalation of product mist may cause respiratory irritation: Symptoms may include nasal discomfort 				
	breath, wheezing	g and coughing.		eactions with symptoms of shortness of . Avoid breathing product mist. Was	
	thoroughly after handling.				
Conditions Aggravated by Use:	•	Use of this product may aggravate preexisting skin; eye and respiratory disorders including asthma and			
	dermatitis.				
Emergency & First Aid Procedures:					
				e contact lenses. Get medical attention.	
Skin:	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists. Wash contaminated clothing before reuse.				
Ingestion:	Do not induce vo	Do not induce vomiting. Drink one or two glasses of water to dilute product. Get medical attention. Do			
		not give anything by mouth to an unconscious person.			
Inhalation:	Move person to f	resh air. Get medica	l attention if irritation pers	sists.	
SECTION VI: REACTIVITY DATA Stability:	Stable		Incompatible Mat	erials: Strong oxidizing agents	
Hazardous Decomposition Products:			Hazardous Polymeriz	zation: Will Not Occur	
Steps to be Taken in Case Material is Released or Spilled:	Small spills of one gallon or less may be flushed with plenty of water to sanitary sewer system (If permitted by local sewer regulations). Dike and contain large spills with inert material and transfer liquid to containers for disposal. Keep spill out of storm sewers and waterways.				
Waste Disposal Method:		Dispose of in compliance with all federal, state and local laws and regulations.			
SECTION VIII: SPECIAL PROTECTION	N INFORMATION	N			
Respiratory Protection:				n occurs, the use of a NIOSH approved ion II should be considered.	
Ventilation:	Provide good ger	Provide good general ventilation. Local exhaust ventilation may be necessary for some operations.			
Protective Gloves(Specify Type):	Rubber or other i	Rubber or other impervious gloves are recommended when handling product.			
Eye Protection(Specify Type):	Splash goggles are recommended when handling product.				
	See 29 CFR 1910.132-138 for further guidance.				
SECTION IX: SPECIAL PRECAUTION	•				
Precautions; Handling & Storing:	Wash thoroughly with soap and water after handling.				
Other Precautions:	Keep out of reach of children.				
© SCC 06/08/2012		Ronald T. Cook	Title:	Manager, Regulatory Affairs	
SPARCLEAN SILVERWARE PRE-SOAK		06/08/2012	Supercedes:		
[57]				55.5 112666	
Ref: 29 CFR 1910.1200 (OSHA)	Changes:	General Review			

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond sellers control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State and Local laws and regulations.