### Total Restaurant Supply - https://totalsupply1.com - Toll Free 1-800-944-9304 - Local 507-288-9454 2940 Hwy 14 W, Rochester, MN 55901

EV9612-22 i2000 <sup>2</sup> Filter Cartridge		
Delivers premium quality water for ice applications		
	i2000² Replacement Cartridge: EV9612-22	<ul> <li>BENEFITS</li> <li>New and improved Micro-Pure II media with AgION<sup>TM</sup> antimicrobial protection inhibits any potential bacterial growth</li> <li>Reduces water-related ice machine problems caused by scale build- up from dirt and dissolved minerals (as tested by Everpure)</li> <li>Reduces chlorine taste and odor and other offensive contaminants</li> <li>Self- contained scale inhibitor feed keeps ice machines functioning at full capacity (as tested by Everpure)</li> <li>Reduces maintenance and service costs by reducing scale* and clogging of distribution lines, evaporator plate and pump (*as tested by Everpure)</li> <li>Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size and reduces health contaminants such as asbestos fibers and Cryptosporidium and Giardia cysts</li> <li>Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination</li> <li>NSF Certified under NSF/ANSI Standards 42</li> </ul>
INSTALLATION TIPS         Install vertically with cartridge hanging down         Allow 2-1/2" clearance below the cartridge for         easy cartridge replacement         Flush cartridge by running water through system         for five minutes at full flow	OPERATION TIPS Change cartridges on a regular 6 month preventative maintenance program Change cartridges when capacity is reached or when pressure falls below to psi Always flush the filter cartridge at time of installation and cartridge change	APPLICATION/SIZING For ice machine applications Rated Capacity: 9,000 gallons (34,068L)

#### Total Restaurant Supply - https://totalsupply1.com - Toll Free 1-800-944-9304 - Local 507-288-9454 2940 Hwy 14 W, Rochester, MN 55901

## S P E C I F I C A T I O N S

Overall Dimensions: 20.75"H x 3.25"Diameter

Service Flow Rate: Maximum 1.67 gpm (6.3 Lpm)

Rated Capacity: 9,000 gallons


Pressure Requirements: 10 - 125 psi (0.7 – 8.6 bar), non-shock

Temperature: 35 - 100°F (2 - 38°C)

No electrical connection required

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.

# i2000<sup>2</sup> Filter Cartridge





System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects Chemical Unit Taste and Odor Reduction Chlorine Reduction Mechanical Filtration Unit Nominal Particulate Reduction, Class I 99.2+% reduction of particles one-half micron and larger in size Standard No. 53: Health Effects Mechanical Filtration Unit Turbidity Reduction Cyst Reduction Asbestos Reduction



Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



EVERPURE, LLC 1040 Muirfield Drive Hanover Park, Illinois 60133 Toll Free (800) 323-7873 Tel (630) 307-3000 Fax (630) 307-3030 http://www.everpure.com In Europe: N.V. EVERPURE (EUROPE) S.A. Industriepark Wolfstee Toekomstlaan 30 B-2200 Herentals Belgium Tel 32 -14-283500 Fax 32-14-283505

#### In Japan:

EVERPURE JAPAN LLC Hashimoto MN Bldg. 7F 3-25-1 Hashimoto Sagamihara-Shi Kanagawa 229-1103 Japan Tel 81-(0)42-775-3011 Fax 81-(0)42-775-3015