



Royal Series Gas Connector Complete Kit

Model: _____ Item #: _____ Date: _____
Project: _____ Qty: _____ Approved By: _____

Product Image



Product Description

The Krowne Metal Gas Connector is a stainless steel hose designed to be used with stationary and caster-mounted commercial kitchen equipment. Its design is convenient for equipment that is routinely moved for cleaning as features such as the rotational end pieces and the included restraining cable provide both ease and durability when moving large gas-supplied equipment.

The green antimicrobial PVC-coated protective layer allows for easy cleaning while the stainless steel corrugated tubing provides both flexibility and a strong internal structure that will last with enduring strength.

Standard Features

- Ends rotate for simple installation and durability
- Heavy duty stainless steel corrugated tubing flexibility for easy installation
- Heavy duty stainless steel radial wrap prevents hose from stretching
- PVC Protective coating with anti-microbial agent for easy cleaning
- Welded construction for added durability

Included Contents

① Gas Hose	Designed for moveable, caster mounted kitchen equipment
② Quick Disconnect	Easily disconnects gas hose to move equipment for maintenance and cleaning
③ Gas Valve	Required by code to allow manual shutoff within 6 ft. of appliance
④ Restraining Cable	Prevents hose from being pulled too far
⑤ Mounting Hardware	All hardware included to mount restraining cable to wall
⑥ 90° Elbows	Elbows included for installation

Size Chart

Interior Size	Length	Model Number	BTU/hr*
1/2"	24"	M5024K	87K
1/2"	36"	M5036K	77K
1/2"	48"	M5048K	68K
1/2"	60"	M5060K	60K
1/2"	72"	M5072K	55K
3/4"	24"	M7524K	232K
3/4"	36"	M7536K	218K
3/4"	48"	M7548K	180K
3/4"	60"	M7560K	158K
3/4"	72"	M7572K	139K
1"	24"	M10024K	414K
1"	36"	M10036K	379K
1"	48"	M10048K	334K
1"	60"	M10060K	294K
1"	72"	M10072K	279K
1-1/4"	24"	M12524K	699K
1-1/4"	36"	M12536K	615K
1-1/4"	48"	M12548K	541K
1-1/4"	60"	M12560K	476K
1-1/4"	72"	M12572K	419K

Certifications



ANSI Z21.41-2014 • CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances

ANSI Z21.69-2009 • CSA 6.16-2009 Connectors For Moveable Gas Appliances

ANSI Z21.69a-2012 • CSA 6.16a-2012 Addenda

Restraining Kits are required by law for all moveable gas equipment



Royal Series Gas Connector Complete Kit

Model: _____ Item #: _____ Date: _____
Project: _____ Qty: _____ Approved By: _____



Replacement Parts

QUICK DISCONNECT



Interior Size	Model #
1/2"	QD50
3/4"	QD75
1"	QD100
1-1/4"	QD125

GAS VALVE



Interior Size	Model #
1/2"	G50
3/4"	G75
1"	G100
1-1/4"	G125

RESTRAINING CABLE & MOUNTING HARDWARE



Interior Size	Model #
24"	R24
36"	R36
48"	R48
60"	R60
72"	R72

90° ELBOWS



Interior Size	Model #
1/2"	E50
3/4"	E75
1"	E100
1-1/4"	E125

Certifications



ANSI Z21.41-2014 • CSA 6.9-2014 Quick Disconnect Devices For Use With Gas Fuel Appliances

ANSI Z21.69-2009 • CSA 6.16-2009 Connectors For Moveable Gas Appliances

ANSI Z21.69a-2012 • CSA 6.16a-2012 Addenda

Restraining Kits are required by law for all moveable gas equipment